

7.5ft & 12.5ft Tail Feather Instruction Sheet

To Install with ground stake:

1. Start by hammering the ground stake (1) into the ground where you want your **Tail Feather Flag** to be installed. Hammer it approximately halfway into the ground. (Use gloves or a thick cloth when handling the ground stake to protect your hands. Also, use a scrap piece of wood between the stake and your hammer to protect the end of the stake from being deformed by the hammer.)

WARNING: WHEN INSTALLING THE GROUND STAKE, EXERCISE CAUTION, AVOIDING ALL ELECTRIC, WATER, AND GAS LINES!

2. Assemble the two lengths of the **Tail Feather** flag pole by inserting the top Flex Tip into the bottom straight pole (2).
3. Thread the assembled pole into the flag sleeve, making sure the top of the pole seats snugly into the furthestmost portion of the sleeve (3), pulling the bottom of the flag sleeve downward along the length of the pole.
4. Push the CoroShield over the ground stake followed by the washer and then slide the flag pole onto the ground stake (4).
5. To finish installation, attach the web loop to clip on the black adjustable cleat (5).

To Install with X-Stand:

1. Follow steps 2–3 above.
2. Open X-Stand until legs are perpendicular to one another (6).
3. Slide metal sleeve over peg on top of the X-Stand (7).
4. Slide flag pole onto the X-Stand and follow step 5 above to finish.

